ansaldo <mark>energ</mark>ia

THE GAS TURBINE: AE94.2

Robust design for top class reliability

16 stages axial compressor with variable guide vane* Rotor Displacement

System (RDS) for gap optimization

Single shaft, internally **aircooled rotor**, disk type with Hirth serration and central tie rod

Cold-end generator



*All vanes and blades replaceable with rotor in place.

Dry low NOx

dual-fuel burners (8 for each chamber)

2 silo-type Combustion Chambers lined with individually replaceable tiles

4 stages, air cooled turbine with axial discharge*

Fast and Flexible

The AE94.2 gas turbine is a benchmark for both operational and fuel flexibility. Its high cycling capability, combined with fast start up and high ramp rates, makes it suitable for peak plants, grid support and dead power grid energization as well.

Fuel diversification

For normal operation it is possible to use up to 40% of hydrogen in fuel gas blends, but the AE94.2 can burn also non conventional fuels (i.e. naphtha, crude and heavy fuel oil, hydrogen rich fuels, coal gases) as well liquid green fuels such as HVO, Methanol and Ethanol. Its special "version K", specifically designed for low and very low BTU fuels, can manage a very wide range of syngas, well gases, coal gases.



ansaldo energia

With more than 120 units installed worldwide and 9 millions of operating hours cumulative through different fuels and load regimes, the AE94.2 shows excellent record of robustness, operational reliability and durability.

Environmentally sustainable

NOx level down to **15 ppm in dry gas mode** and **75 ppm in dry oil mode** (with possibility to reach **25 ppm** with small water amount).

Smart maintenance approach

- Extended 41 kEOH inspection interval for hot gas components
- Possibility to replace vanes and blades with rotor in place
- Immediate accessibility into the combustion chambers for checks and repairs

Maximized availability to ensure the best revenues for our Customers.

Customized service agreements, including upgrading packages, allow Customers to choose the best solution for their needs.

Natural gas ISO conditions	AE94.2 Performance	Power Plant Configuration	1+1	2+1
Power output (MW)	190	CC Net Output (MW)	287	578
Efficiency (%)	36.8	CC Net Efficiency (%)	55.8	56.2
Exhaust Mass Flow (Kg/s)	555	CC Net Heat Rate (kJ/kWh)	6,450	6,405
Exhaust Temperature (°C)	550	Plant Turndown	45	25
GT minimum load (%)	40	Minimum load (%)	т у	23

General note: Performance data are calculated with 100% methane (LHV) at ISO conditions, direct cooling.

References: 120+ units total > 10 millions EOH For more information, please visit www.linkedin.com/company/ ansaldo-energia

Via N. Lorenzi, 8 16152 Genoa - Italy Tel: +39 010 6551 ansaldoenergia.com Ansaldo Energia, all rights reserved. Trademarks mentioned in this document are the property of Ansaldo Energia, its affiliates, or their respective owners in the scope of registration. The information contained in this document is merely indicative. No representation or warranty is provided, nor should be relied on, that such information is complete or correct or will apply to any particular project. This will depend on the technical and commercial circumstances. Said information is provided without liability and is subject to change without notice. Reproduction, use or disclosure to third parties, without express written authority, is strictly prohibited.